

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-165-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

31,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 430 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-166-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

31,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 431 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-166-1; Apr 6 2010 9:23AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-167-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

31,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 432 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-168-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

31,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 433 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-169-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

31,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 434 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-169-1, Apr 6 2010 9:23AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-170-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

31,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 435 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-171-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 347 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-171-1: Apr 6 2010 9:23AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-172-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 348 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine; this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-172-1: Apr 6 2010 9:24AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-173-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 349 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-174-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 350 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD.(EAST FACILITY),LODI, CA 95242

N-4939-174-1 App 6 2010 9 24AM - SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-175-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 351 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-176-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 352 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-177-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 353 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-178-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 354 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-179-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 355 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-180-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 356 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-180-1: Apr 6 2010 5:24AM - SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-181-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 357 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-181-1: Apr 6 2010 9:24AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-182-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 358 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-183-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 359 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-183-1: Apr 6 2010 9:24AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-184-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 360 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-184-1: Apr 6 2010 9:25AM -- SIONGCOU

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-185-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 377 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-185-1 : Apr 6 2010 9:25AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-186-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 378 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-187-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 379 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-187-1 Apr 6 2010 9:25AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-188-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

41,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 380 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-188-1; Apr 6 2010 5:25AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-189-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 49 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-190-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 50 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-191-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 71 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-192-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 72 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD.(EAST FACILITY),LODI, CA 95242

N-4939-192-1: Apr 6 2010 9:25AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-193-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 73 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-193-1; Apr 6 2010 9:25AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-194-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 74 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-195-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 75 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-196-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

59,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 436 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-197-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

59,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 437 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-197-1: Apr 6 2010 9:26AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-198-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

59,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 438 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-198-1 - Apr 6 2010 9:26AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-199-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

59,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 439 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-199-1; Apr 6 2010 9 26AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-200-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

59,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 440 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD (EAST FACILITY), LODI, CA 95242

N-4939-200-1: Apr 6 2010 9:26AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-201-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

59,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 441 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-201-1 Apr 6 2010 9:26AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-202-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

59,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 442 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-202-1 Apr 6 2010 9:26AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-203-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

59,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 443 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-203-1 : Apr 6 2010 9 26AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-204-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 381 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4535-204-1 : Apr 6 2010 9:26AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-205-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 382 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-205-1 : Apr 6 2010 9:26AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-206-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 383 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-206-1 : Apr 6 2010 9:26AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-207-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 384 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-208-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 385 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-209-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 386 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-210-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 387 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-210-1 : Apr 6 2010 9:27AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-211-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 388 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD (EAST FACILITY), LODI, CA 95242

N-4939-211-1 : Apr 6 2010 9:27AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-212-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 389 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-213-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 390 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-214-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 391 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-214-1 : Apr 6 2010 9:27AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-215-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 392 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-215-1; Apr 6 2010 9:27AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-216-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 393 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-217-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 394 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-218-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 395 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-218-1: Apr 6 2010 9:27AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-219-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 396 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C.W. US INC DBA TURNER ROAD VINTNERS
Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242
N-4939-219-1 Apr 6 2010 9:28AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-220-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 397 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-221-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 398 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-222-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 399 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-223-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-224-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-225-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-226-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-226-1: Apr 6 2010 9:26AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-227-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-228-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-229-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 407 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-229-1: Apr E 2010 9:28AM -- SIOGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-230-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 408 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-231-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 409 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-231-1: Apr 6 2010 9:26AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-232-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 410 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-232-1 : Apr 6 2010 9:25AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-233-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-234-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 412 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-235-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

60,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-236-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 329 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-237-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 330 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-237-1 : Apr 6 2010 9:29AM - SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-238-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 331 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-238-1 : Apr 6 2010 9 29AM -- SICNGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-239-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 332 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-239-1: Apr 6 2010 9:25AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-240-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 333 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-241-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 334 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-241-1 : Apr 6 2010 9:25AM - SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-242-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 335 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-243-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 336 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-244-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 337 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-245-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 338 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD (EAST FACILITY), LODI, CA 95242

N-4939-245-1; Apr 6 2010 9:30AM - SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-246-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 339 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-247-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 340 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-248-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 341 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-249-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 342 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-250-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 343 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD,(EAST FACILITY),LODI, CA 95242

N-4939-250-1; Apr 6 2010 9:30AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-251-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 344 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-251-1 Apr 6 2010 9:30AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-252-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 345 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4639-252-1 : Apr 6 2010 9:30AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-253-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

62,800 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 346 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS
Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242
N-4939-253-1 : Apr 6 2010 9:30AM -- SONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-254-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

69,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 51 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-255-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

69,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 52 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: C W US INC DBA TURNER ROAD VINTNERS

Location: 4614 WEST TURNER ROAD, (EAST FACILITY), LODI, CA 95242

N-4939-255-1: Apr 6 2010 9:31AM -- SIONGCOJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-256-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

69,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 53 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-257-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

69,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 54 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-258-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

69,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 55 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-4939-259-1

EXPIRATION DATE: 08/31/2009

EQUIPMENT DESCRIPTION:

122,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 455 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When storing wine, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1]
2. When this tank is used for storing wine, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1]
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2]
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and fermentation emission reductions. The information shall be recorded by the tank Permit To Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

These terms and conditions are part of the Facility-wide Permit to Operate.